

| Division of Mo | odel | | | | | | | | |
|-------------------|--------------------------|-------|------|------------------|-----------------|-------------|-------------------|-------|--------|
| Model | Head Interval [mm] | Color | Head | Y-Stroke [mm] | Emb. Space [mm] | | Machine Size [mm] | | |
| | | | | | Each Head | All Head | Length | Width | Height |
| SWF/E-WB(X)630-68 | 240[480] | 6 | 30 | 680 | 240[480] x 680 | 7,200 x 680 | 8,880 | 1,970 | 1,742 |

| Sp | ecifications | | | | | | |
|-------------------------------|--------------|--|-------------------------|-----------------|--|--|--|
| Speed | | 850 rpm | | | | | |
| Stitching Length | | 0.1 ~ 12.7 mm | | | | | |
| Embroidering Range [X x Y] | | General | 240 mm[480 mm] x 680 mm | Overlan : 40 mm | | | |
| | | AFC | 240 mm[480 mm] x 550 mm | Overlap : 60 mm | | | |
| Motor | Main | Servo Motor x 1 | | | | | |
| Motor | X-Y | Servo Motor x 2 | | | | | |
| Electricity | | 1-Phase 200V, 220V, 240V [50/60Hz] | | | | | |
| | | 3-Phase 200V, 220V, 240V, 350V, 380V, 415V [50/60Hz] | | | | | |
| Power Consumption | | 1.5 kW | | | | | |
| Work Specification | | Specification[thick and thin fabrics] | | | | | |
| Maximum Roll Size | | 120 Inch x 2 Roll | | | | | |
| Bobbin Winder | | Standard | | | | | |
| Operation Box | | Standard : Color LCD Screen | | | | | |
| Hook | | Standard Hook | | | | | |
| Memory Capacity | | Standard : 4,000,000 stitches | | | | | |
| Memory Media | | USB Memory Stick | | | | | |
| Safety Device | | Standard : Emergency Stop, Error Code Message | | | | | |
| Optional Device | | Fabric, Floor, Roll Up | | | | | |

All information is based on data available at the time of publication and subject to change without previous notice.

Overseas network

USA

SUNSTAR U.S.A. INC

11475 N.W. 39th St. Miami, Florida, 33178, USA tel: 1-305-591-9596 fax: 1-305-591-0661

CHINA

| FOSHAN SUNSTAR PRECISION CO., LTD. |

China's Nanhai District, Foshan City, Guangdong Province, Songgang Shishan Town Industrial Zone, on the sand the water

tel: **86-757-8520-7222** fax: **86-757-8523-0468**

EUROP

SUNSTAR MACHINERY EUROPE GMBH

IZ NOE-SUED - Strasse 7, Obj. 58/D3 A-2355 Wiener Neudorf, Austria

tel: 43-2236-660-229 fax: 43-2236-660-2293

■ EGYPT

| SWF CAIRO BRANCH OFFICE | tel: 20-2-2702-0772 | fax: 20-2-2702-3859

■ TURKEY

SWF TURKEY ISTANBUL BRANCH OFFICE | tel: 90-212-438-1525/1530 fax: 90-212-438-1546

■ SAUDI ARABIA

| SWF JEDDAH OFFICE | tel: 966-2627-0589 | fax: 966-2647-7164

■ PAKISTAN

| SWF LAHORE BRANCH OFFICE | tel: 92-322-4887443

■ BANGLADESH

| SWF DHAKA BRANCH OFFICE | tel: 88-02-881-9153 | fax: 88-02-883-5707

■ SYRIA

| SWF ALEPPO BRANCH OFFICE | tel: 963-21-267-6590 fax: 963-21-264-4978

■ INDI

| SWF BANGALORE BRANCH OFFICE |
tel: 91-80-4152-4101 | fax: 91-80-4152-4103
| SWF DELHI BRANCH OFFICE |
tel: 91-12-0426-0733 | fax: 91-12-0426-0734
| SWF SURAT BRANCH OFFICE |
tel: 91-26-1308-0737 | fax: 91-11-4050-3634


■ VIETNAM

| SWF HOCHIMINH BRANCH OFFICE | tel: 84-8-3592-1588/84-8-3504-3472 fax: 84-8-3592-1587

[SWF HANOI BRANCH OFFICE | tel: 84-4-8587-2751/84-4-3783-4532 fax: 84-4-3783-4533

■ INDONESIA

| SWF JAKARTA BRANCH OFFICE | tel: 62-021-451-3601~2 fax: 62-021-451-6552



AFC SERIES

Multi-heads quilting embroidery machines

New standards for quilting embroidery business





SUNSTAR CO., LTD.

Head office #178-67, GAJWA-DONG, SEO-GU, INCHEON, KOREA tet +82(0)32 580 5980-93 fax +82(0)32 579 8350-51 **www.sunstar.co.kr**









New standards for

Quilting embroidery business

- 1 New control and X-Y driving mechanism
- ∩2 | Powerful material presser device and clamp
- 03 | Improved quality and varied materials
- 1 Possible to embroider various range from thin to thick materials
- ∩5 | Upgraded clamp (X, Y clamp)

Operation

- Expanded Memroy Size
- Enlarging and Reducing Design
- Automatic Selection of Needle Bar
- General / Special Repetition Work
- Automatic / Manual Offset
- Return to Start Point

- Float Stitch Function
- Frame Backward
- Automatic Return to Stop Point in Unexpected Blackout
- Editing Function
- Individual Head Operation
- Mirror Image Conversion and Design Direction



Technology



 Strong clamping enables accurate embroidery on thick as well as thin materials.



HOLDING SYSTEM

 Powerful air cylinderes are able to hold perfectly regardless of fabric's size.

▲ model: E-WB(X)630-68



SUB CONTROL DEVICE

Roll Up Stand

THE PERSON NAMED IN COLUMN TO STATE OF THE PERSON OF THE P

 Sub control device with ratchet type detects not only upper thread breakage but also under thread volume on the bobbin.



START/STOP SWITCH

Fabric Stand

 By start/ stop switch installed on the back of machine, material is provided smoothly.



STRETCHING STRUCTURE

1) By stretching structure, material can be stretched, and accurate embroidery come true.



ROLL DEVICE

 To embroider continually, roll for wring and providing material are installed.



UPPER THREAD CATCHER

 An intergrated and single motorbased upper thread holder ensures smooth and accurate operation and stable storage of the thread.

It also minimized the noise during operation.



X-Y DRIVER

 SWF offers an exclusive "track roller" system of X and Y drive for accurate power delivery and semi-permanent precision of embroidery.



Floor